

# Mobil Vacuoline 500

## Circulating Oils

### Product Description

The Mobil Vacuoline 500 Series family of products provides a versatile lubricant source for a wide range of industrial equipment. The Mobil Vacuoline 500 Series of lubricants are high performance heavy duty circulating oils designed for the demands of No-Twist Rod mills, however their all round performance makes them an excellent choice for circulation systems lubricating gears and bearings. Mobil Vacuoline 500 Series are designed to meet the critical requirements of the Morgan Construction Company's high speed No-Twist Rod Mills, as well as the circulation oil requirements of Danielli rod mills.

They are formulated from high quality base stocks and a proprietary additive system to provide superior wettability, extra oil retention and thin film protection against rust and corrosion. Mobil Vacuoline 500 gives excellent resistance to oxidation and thermal degradation, and a high level of protection against wear. They possess excellent demulsibility that permits water and other contaminants to separate readily from the oil in the system reservoir. The Mobil Vacuoline 500 Series are available in six viscosity grades.

### Features and Benefits

The Mobil Vacuoline 500 Series family of products is well known and highly regarded world-wide based on their outstanding performance and the Research and Development expertise and global technical support which stand behind the brand. The highly versatile performance of Mobil Vacuoline 500 Series oils, has made them the choice of many users around the world for many decades.

Mobil Vacuoline 500 series are designed for lubrication of circulation systems of No-Twist Rod Mills, industrial and marine gearboxes, hydraulic systems plus a wide variety of ancillary equipment.

Features	Advantages and Potential Benefits
Good protection against rust and corrosion through a balanced high performance lubricant formulation	Fewer unscheduled stoppages and lower maintenance costs
Outstanding antiwear performance	Excellent protection of critical bearings and gears
Excellent water separation characteristics	Rapid separation of water for smooth, efficient operation, reduced downtime and undiminished wear protection
High resistance to oxidation and thermal degradation	Long oil change life and avoidance of costs of unanticipated production interruptions
Multiple application capability	Inventory Savings

### Applications

These oils are intended primarily for the lubrication of plain bearings, roller bearings, parallel shaft and bevel gearing. They are suitable as multipurpose lubricants in systems not subject to shock loading and which do not require extreme pressure performance. The Mobil Vacuoline 500 series possess good demulsibility that is retained under conditions of severe water contamination. Mobil Vacuoline 500 series are used in applications using splash, bath and ring oil arrangements and all other application methods involving pumps, valves and



auxiliary equipment. They are recommended for use in hydraulic systems where higher viscosity oils are specified. They are particularly resistant to the effects of prolonged high temperature exposure and perform well in circulating systems with short oil residence times.

Typical applications include

- No Twist Rod Mills
- Moderate duty spur, bevel, helical and herringbone gear units
- Circulating systems
- Mobil Vacuoline 525, 528, 533 can also be used in hydraulic systems employing gear, vane, radial and axial piston pumps where high viscosity anti-wear hydraulic fluids are required.
- Certain compressors and vacuum pumps handling air and inert gases provided the discharge temperatures do not exceed 150°C, not suitable for breathing air compressors

## Specifications and Approvals

<b>Mobil Vacuoline 500 Series meets or exceeds the following industry specifications:</b>	<b>525</b>	<b>528</b>	<b>533</b>	<b>537</b>	<b>546</b>	<b>548</b>
Morgan Construction Company's "No-Twist® X Rod Mill Lubricants Specification						

## Typical Properties

<b>Mobil Vacuoline 500 Series</b>	<b>525</b>	<b>528</b>	<b>533</b>	<b>537</b>	<b>546</b>	<b>548</b>
ISO Viscosity Grade	-	150	220	320	460	680
Viscosity, ASTM D 445						
mm <sup>2</sup> /s @ 40°C	89	146	215	309	453	677
mm <sup>2</sup> /s @ 100°C	10.7	14.4	18.8	24.4	29.4	36.9
Viscosity Index, ASTM D 2270	99	96	96	96	95	89
Pour Point, °C, ASTM D 97	-24	-21	-15	-12	-12	-9
Flash Point, °C, ASTM D 92	264	272	284	288	286	286
Specific Gravity @15.6 °C kg/l, ASTM D 1298	0.88	0.89	0.89	0.89	0.90	0.92
Demulsibility at 82°C, ASTM D1401 Minutes to 3ml	15	10	15	20	25	5
Demulsibility for non-EP oils, ASTM D2711, ml water	39	38	36	39	35	36
Rust Protection, ASTM D665						
Distilled Water	Pass	Pass	Pass	Pass	Pass	Pass
Sea Water	Pass	Pass	Pass	Pass	Pass	Pass
Foaming Characteristics, ASTM D 892Seq I, II, III; Tendency/Stability, ml/ml						
Seq I	10/0	5/0	5/0	10/0	5/0	0/0
Seq II	0/0	0/0	0/0	0/0	0/0	0/0
Seq III	0/0	0/0	0/0	0/0	0/0	0/0

<b>Mobil Vacuoline 500 Series</b>	<b>525</b>	<b>528</b>	<b>533</b>	<b>537</b>	<b>546</b>	<b>548</b>
Copper Corrosion, ASTM D130 3 hours @ 100°C	1A	1A	1A	1A	1A	1A
FZG Gear Test, DIN 51354, Failure Stage	12	12	12	12	12	12

## Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Toxicity class: free BAG T No.: 611500

*The Mobil logotype, the Pegasus design and Vacuoline are trademarks of Esso Mobil Corporation, or one of its subsidiaries.*